TEL: +81-3-6260-2012

IND-5526-2007E

ANTIRUST TERAMI SC-W

Barium-free solvent-diluting cleaning and rust preventive oil for strong displacement of water after water cutting work

ANTIRUST TERAMI SC-W is a temporary rust preventive oil with excellent cleaning and water displacement properties. It rinses and removes cuttings and wear particles after cutting and grinding processes using water-soluble fluids.

SPECIAL FEATURES

1. Excellent Water Removal Property

ANTIRUST TERAMI SC-W is ideal for cleaning metal objects after metalworking. ANTIRUST TERAMI SC-W should be applied with immersion coating methods.

2. Superior Rust Prevention

ANTIRUST TERAMI SC-W delivers excellent protection from rust due to the most suitable mineral oil and additives.

3. Low Risk of Fire

ANTIRUST TERAMI SC-W has a high flash point (84°C) although it contains solvents. So it can be used with low risk of fire.

4. Good Removal

Film of **ANTIRUST TERAMI SC-W** is easily removed with organic solvents or alkaline detergents.

5. Easy to Use

ANTIRUST TERAMI SC-W is not sticky because petrolatum is not contained and excellent in the working efficiency. Moreover, it is easy to pass through a filter.

APPLICATIONS

For various processing parts and machine parts

OCCUPIED METHOD

Immersion

CONTAINERS

200-liter drums and 20-liter pail cans.

● Typical Properties of ANTIRUST TERAMI SC-W

Appearance			Light yellow liquid
Color	(ASTM)		L1.0
Density	(15°C)	g/cm ³	0.801
Flash point	(PM)	°C	84
Viscosity	(40°C)	mm^2/s	1.9
Water displacement	(JIS K2246)		No rust
Metal strip corrosion	(JIS K2246 N	P-3)	Passed
Humidity cabinet test	(Class A holding time)	h	>720
Protection	(Indoors)	weeks	2
Type of film			Semi-dry and transparent film
Film thickness		μm	< 1.0

Note: The typical properties may be changed without notice. (March 2011)

■ STORAGE PRECAUTIONS

Store this oil indoors whenever possible. If it is exposed to winter weather or cold temperatures, its film-strengthening agents may separate from the oil in rare instances. If the film-strengthening agents do separate, stir the oil thoroughly before using.



Handling Precautions

lacksquare Follow these precautions when handling this product.

Composition:	Base Oil, Additives
Precautionary pictograms:	
Signal word:	Danger
Hazard Statement:	Combustible liquid
	Causes skin irritation
	Causes serious eye irritation
	May be fatal if swallowed and enters airways
Precautionary Statements:	• Do not handle until all safety precautions have been read and understood.
Prevention	• Wear protective gloves/protective clothing/eye protection/face protection.
	• Do not allow the eyes to become exposed to the product. Do not swallow the product.
	• Keep away from heat/sparks/open flames/hot surfaces – No smoking.
	• Use explosion-proof electrical/ventilating/lighting/equipment.
	Ground/bond container and receiving equipment.
	• Wash hands thoroughly after handling.
	• Do not eat, drink or smoke when using this product.
Response	• IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	• IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and
	immediately contact a physician.
	• IF ON SKIN: Wash with plenty of soap and water.
	Take off contaminated clothing and wash before reuse.
	• If skin irritation occurs : Get medical advice/attention.
	• IF IN EYES: Rinse continuously with water for several minutes.
	• Remove contact lenses if present and easy to do. Continue rinsing.
	• Do NOT induce vomiting.
	• In case of fire: Use suitable extinguishing media for extinction.
Storage	• The product must be stored in a cool, well-ventilated location where it will not be exposed
	to direct sunlight.
	Containers that have been opened must be tightly sealed.
	Store in a well ventilated place. Keep cool.
	Store locked up.
Disposal	• Dispose of contents/container in accordance with local/regional/national/international
	regulations.
	• If there are any doubts about proper methods of handling the product, contact the point of
	purchase before proceeding with usage.