IND-5522-2007E

### **ANTIRUST TERAMI SC**

# Barium-free solvent-diluting cleaning and temporary rust preventive oil

**ANTIRUST TERAMI SC** is Barium-free solvent-diluting cleaning and temporary rust preventive oil, which was developed through many years of research, and its superior performance has been proven in a wide range of applications. **ANTIRUST TERAMI SC**, which does not contain petrolatum, provides good working efficiency, good cleaning performance and high protection performance against corrosion and oil stain.

#### • SPECIAL FEATURES

#### 1. Excellent Rust Prevention

**ANTIRUST TERAMI SC** delivers excellent protection from rust due to the most suitable mineral oil and additives.

#### 2. Low Risk of Fire

**ANTIRUST TERAMI SC** has a high flash point although it contains solvents. So it can be used with low risk of fire.

#### 3. Good Removal

**ANTIRUST TERAMI SC** can be easily removed by using a petroleum solvent or alkaline process cleaner.

#### 4. Easy to Use

**ANTIRUST TERAMI SC** is not sticky because petrolatum is not contained and excellent in the working efficiency. Moreover, it is easy to pass through a filter. It is expected that quantity of application will be decreased.

#### APPLICATIONS

For various processing parts and machine parts

#### **■ STORAGE PRECAUTIONS**

When ANTIRUST TERAMI SC is left in a cold place in winter etc., some of the additives might be separated very unusually. So, it should be kept indoors. When oil separation might occur, please stir well before using.

#### COATING METHODS

Immersion, Spraying, Brushing

#### CONTAINERS

200-liter drums and 20-liter cans

#### Typical Properties of ANTIRUST TERAMI SC

Appearance			Light yellow liquid
Color	(ASTM)		L2.5
Density	(15°C)	g/cm <sup>3</sup>	0.809
Flash point	(PM)	°C	85
Viscosity	(40°C)	$mm^2/s$	2.4
Water displacement	(JIS K2246)		No rust
Metal strip corrosion	(JIS K2246 N	P-3)	Passed
Humidity cabinet test	(Class A holding time)	h	>720
Protection	(Indoors)	months	3
Type of film			Semi-dry and transparent film
Film thickness		μm	1.5

Note: The typical properties may be changed without notice. (June 2010).



## Handling

## **Precautions** ▼ Follow these precautions when handling this product.

Composition:	Base Oil, Additives	
Precautionary pictograms:		
Signal word:	Danger	
Hazard Statement:	Combustible liquid	
	May be fatal if swallowed and enters airways	
Precautionary Statements:	Do not handle until all safety precautions have been read and understood.	
Prevention	Wear protective gloves/protective clothing/eye protection/face protection.	
	• Do not allow the eyes to become exposed to the product. Do not swallow the product.	
	Keep away from heat/sparks/open flames/hot surfaces – No smoking.	
	Use explosion-proof electrical/ventilating/lighting/equipment.	
	Ground/bond container and receiving equipment.	
	Wash hands thoroughly after handling.	
	• Do not eat, drink or smoke when using this product.	
Response	• IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	
	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
	• If the eyes are exposed to the product: Rinse the eyes with plenty of running water and	
	immediately contact a physician.	
	• IF ON SKIN: Wash with plenty of soap and water.	
	• Do NOT induce vomiting.	
	• In case of fire: Use suitable extinguishing media for extinction.	
Storage	• The product must be stored in a cool, well-ventilated location where it will not be exposed	
	to direct sunlight.	
	Containers that have been opened must be tightly sealed.	
	Store in a well ventilated place. Keep cool.	
	Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international	
	regulations.	
	• If there are any doubts about proper methods of handling the product, contact the point of	
	purchase before proceeding with usage.	